

OC2 Temperature Controller

version 2.0/2015



The **Covesion OC2** temperature controller is a compact stand-alone benchtop unit for use with our PPLN oven range.



Key Features

- Simple push button interface
- Set point stability $\pm 0.01^\circ\text{C}$
- Set point resolution 0.01°C
- Maximum temperature 200°C
- PC control interface via USB
- Auto-detect feature for all Covesion PPLN crystal ovens

Covesion's user-friendly OC2 is specially designed for use with our PPLN crystal ovens. The auto-detect feature provides hassle-free, plug-and-play functionality. The user can simply dial in the required temperature and allow the oven to reach optimum stability.

The OC2 provides high long term thermal stability of $\pm 0.01^\circ\text{C}$ for all temperatures from 30 to 200°C (see data below). This level of stability is typically achieved within only a few minutes of reaching the set point temperature.

The combination of long term stability and low set point resolution of 0.01°C ensures that optimised conversion efficiency can be maintained with our PPLN products.



Copyright © 2015 Covesion Ltd

email: sales@covesion.com
web: www.covesion.com

tel: +44 (0)1794 521 638
fax: +44 (0)8709 289 714


covesion

OC2 Temperature Controller


version 2.0/2015

PC control

The OC2 offers direct control from a PC via a software application or through **LabVIEW** drivers. This will enable Covesion MgO:PPLN crystals to be fully integrated into an optical system for automated control.

Furthermore an **OC1 upgrade package, OC1-USB**, is available for existing controllers which will enable the same functionality.

- Standard USB type B connector
- Covesion OC2 software application with GUI
- Data saved to .csv format
- Features slow ramping via the Cycle Mode for finding SHG phase matching peak.
- LabVIEW drivers
- PC control upgrade kit available for OC1 units



Specifications

Parameter	Min	Typ	Max	Unit
Input voltage	88		264	VAC
Output power			35	WDC
Output voltage			24	VDC
Temperature control range ¹	15		200	°C
Set-point resolution	0.01			°C
Absolute temperature accuracy ²		±0.1		°C
Temperature stability (24 hour) ³		±0.01		°C
Heating time from ambient to 200°C		7		minutes
Cooling time from 200°C to 60°C ⁴		20		minutes
Cooling time from 60°C to 30°C ⁴		20		minutes
Operating temperature (external)	10		50	°C
External Dimensions (L x W x H)		199 x 158 x 74		mm
Weight		1.1		kg

1. Covesion oven types are suitable for heating only. The external oven temperature must be lower than the set-point temperature.

2. Does not account for sensor tolerances.

3. From 5°C above ambient temperature to 200°C

4. Room temperature at 25°C.